

## TIBALOK

The hydraulic quick coupler enables quick tool changes on the excavator.

It is a specialized device for connecting and disconnecting excavator hydraulic lines and their associated attachments, such as tilt buckets, sorting grabs, hydraulic compactors, and more.

The TIBALOK system is mounted onto an existing hydraulic quick coupler and turns it into a fully hydraulic quick coupler. Optional 7-pin electrical connector available.

TIBALOK can be mounted on various well-known quick couplers, such as D-Lock, S-Lock Coupler, PIN LOCK and others.

Suitable for excavators in the 10–60 t class. Installation on wheel loaders from 5–30 t available upon request.

# TIBALOK



# Technical Specifications

|                 |               |
|-----------------|---------------|
| Line Connection | 2 x 1 inch    |
| Oil Flow        | 160–240 l/min |
| Line Connection | 3 x 1/2 inch  |
| Oil Flow        | 40–60 l/min   |

## IN SHORT:

Our specialized device for connecting and disconnecting hydraulic lines on excavators and wheel loaders.

- Tool changes in under 10 seconds
- Cost savings compared to system replacement
- Retrofit kit for existing quick couplers
- Controlled directly from the cab
- Suitable for excavators from 10–60 ton class and wheel loaders from 5–30 ton



LEARN MORE:

